




# EzAttend 10

## Access control



## TECHNICAL SPECIFICATIONS



### Readers and Identification Features

- Facial Reader: capacity for up to 50,000 faces.
- Biometric Reader: capacity for up to 100,000 biometrics.
- **RFID Reader:** Compatible with 125 kHz Unique proximity cards with capacity for up to 50,000 cards.
- Password: Capacity for up to 50,000 passwords.
- QR Code Reader: QR Code reader feature.
- Other Identification Modes: ID number entry with password confirmation.
- Palm recognition feature.

### Communication

- Native Connections: TCP/IP, USB, and Wi-Fi.
- Communication in Server or Client modes.
- Embedded management system, accessible via web browser.
- HTTPS communication protocol for enhanced security.

### Display and Camera

- Dual Camera: Sony HD 2MP color WDR camera and 2MP infrared camera.
- Display: 10.1" capacitive color touchscreen (HD 1280x800).
- Processor: DUAL CORE ARM CORTEX-A7, 12000G (1.2T).
- RAM: 1GB DDR3.
- ROM: EMMC FLASH 8GB.
- Voice command for performed operations.
- 200W infrared binocular camera.
- Fast Face Capture with light balancing feature.





## OPERATIONAL FEATURES

- ▶ Capacity for up to 500,000 logs/records.
- ▶ Advanced anti-fraud technology to prevent recognition via photos or videos.
- ▶ Support for up to 10 users with configurable administrative permissions.
- ▶ Supports up to 30 characters for user IDs.
- ▶ Configurable departments and independent rules per user.
- ▶ Simultaneous identification of multiple users.
- ▶ Recognition speed under 1 second.
- ▶ Screen lock function, which can be activated by proximity or touch.
- ▶ Siren/Buzzer activation at pre-determined times.
- ▶ Support for Master Card registration.
- ▶ **Adjustable Range:** 3 configurable distance levels for facial reading.
- ▶ "Save Photo" feature to store images of all users who accessed or approached the camera.
- ▶ 1 Push-button input (Request-to-Exit).
- ▶ 1 Door sensor input (Open door/Forced entry alert).
- ▶ **1 Internal Relay:** rated up to 250VAC/3A.
- ▶ 1 Emergency sensor input.
- ▶ 1 Wiegand Input and 1 Wiegand Output.
- ▶ 1 External doorbell or siren output.
- ▶ 1 Native USB 2.0 port for importing/exporting configurations and logs.
- ▶ **Configuration available in 3 languages:** Portuguese, English and Spanish.





## ENVIRONMENT

- ▶ **Operating temperature:** -10°C to +45°C.
- ▶ **Humidity:** 10% to 95% (non-condensing).
- ▶ **Ambient light:** 0 to 50,000 Lux.

## ELECTRICAL

- ▶ **Power Supply:** 12 ~ 14.5V switching.
- ▶ **Maximum Current:** 520mA.
- ▶ **UPS (Nobreak):** battery backup with up to 4 hours of autonomy (Optional).



## DIMENSIONS

• **Weight:** 0.850 kg

• **Packed weight:** 1.245 kg

• **Height:** 300.00 mm

• **Depth:** 23.50 mm

• **Width:** 165.00 mm

